



SPECIALISED PRINTER

The **PR4 SR** is a **two station dot matrix printer**, intended for applications where the journal is not requested, which can handle individual forms (slips) and a single paper roll.

The first station prints either **receipts or the journal** (a duplicate copy roll must be used if both types of document are required); the second station prints **transaction slips**, inserted either from the top or the front.

In any retail application - from hypermarkets or large department stores to small shops - the operations performed by the printer play a key role. **PR4 SR** is an **easy-to-use specialised printer**, which ensures reliability and autonomy.

The printer can also mount an optional **MICR reader**.

DESCRIPTION

PR4 SR offers **advanced capabilities**, outstanding productivity in printing and paper management, **low noise level** and high operating speed that makes it a top performer in its market class.

This two -station model intended for applications where the journal is not requested- handles **individual forms** and a **single paper roll** for widths of up to 140mm.

The first station prints either receipts or the journal (a duplicate copy roll must be used if both types of documents are required), the second station prints transaction slips, inserted from the top or the front.

MAIN CHARACTERISTICS

-  TWO STATIONS IMPACT DOT MATRIX PRINTER FOR RECEIPT AND TRANSACTION SLIPS
-  FLEXIBLE PAPER MANAGEMENT
-  WIDE RANGE OF OPTIONS
-  EXCELLENT PRODUCTIVITY

TECHNICAL SPECIFICATIONS

GENERAL CHARACTERISTICS

Technology	Dot matrix, 9 pins
Spacing (dpi)	12, 15, 17.1 dpi (Olivetti) 12.5, 16.7 dpi (Epson)
Speed	250/357 cps
Noise level	less than 66 dB (A)
Characters per line (12dpi)	<i>Receipt</i> • 66 characters per line <i>Journal</i> • 66 characters per line
Paper handling	• Manual cutter • Autoloading
Printed line length	Receipt or journal: 5.5" Front or top insertion: 5.5"
Front document alignment	automatic
Slip introduction	from front/top
Cheque introduction	from front/top
Number of copies	1 + 4
Number of rolls	1
Roll diameter	85 mm
Roll width	76, 83, 115, 140 mm
Emulations	EPSON TM-U925 Olivetti
Interface	RS232C, Parallel, USB
Electrical characteristics	Internal full range (110/240V) External (240V) Absorption (max.): 70 W
Dimensions (WxDxH)	250 x 253 x 183 mm
Weight	4,5 kg
Drivers	Windows 95/98/W2K/NT4.0/W7
Accessories	Ribbon cartridge 7 million characters
Options	• MICR reader • Customer display and cash drawer interface • External slip paper guide • Journal cover with lock

* Product performances are referred to an appropriate use under optimal conditions. With the right to change technical specifications. The registered trademarks are the property of their respective owners.

