



SPECIALISED PRINTER

As the most competitive product on the market today, **PR9** specialised printer is designed to be the **most advanced solution for banking transaction and financial services**.

PR9 offers users the **low cost of ownership**. The long lasting, heavy duty print head with life of more than 550 million dots per needle assures consistent and outstanding performance.

DESCRIPTION

PR9 handles a **wide type of formats and thickness**: single sheet up to A4 size, passbooks, vouchers, tickets, multi-copy forms, etc. Its superior document handling (auto alignment and auto document thickness adaption) capability ensures a **quick and efficient processing** on the documents inserted with variable thickness at different angles in any position.

PR9 fits into your existing IT environment thanks to a comprehensive range of industry standard and financial emulations. It offers a **wide variety of optional devices**, such as scanner, RFID, HMSR and MICR, which greatly contribute to expand its functionality and range of applications.

MAIN CHARACTERISTICS



SUPERIOR DOCUMENT HANDLING CAPABILITIES



LOW COST OF OWNERSHIP



EASY INTEGRATION

TECHNICAL SPECIFICATIONS

GENERAL CHARACTERISTICS

Technology	24 pin dot matrix (550 Million dots/needle life)
Resolution	240 x 360 dpi
Fonts	HSD, Draft, Roman, Sans Serif, Italic OCR-A, OCR-B, E13B
Pitch	10, 12, 13.8, 15, 16.6, 17.1, 18, 20, 30 cpi
Printing speed at 10 cpi	VHSD: 570 cps - HSD: 510 cps Draft: 400 cps NLQ: 200 cps - LQ: 150 cps
Line length	238.8 mm (94 columns at 10 cpi)
Line spacing	1/5", 1/6", 1/8", n/72", n/180", n/216", n/240", n/360"
Copies	1 original + 6 copies
Emulation	IBM PP II & X24, PR2/PR40+, OKI 5530SC LQ 1600K, IBM 9068, IBM 4722, Hitachi
Document Handling	• Feed width: 245 mm • Completely flat paper bed • Automatic insertion with auto-border • Automatic document-thickness adaption

Ribbon cartridge	Standard: 3.5 million Optional: 5 and 10 million characters
Interface	Standard: Serial RS-232 Optional: IEEE 1284 Parallel, USB2.0, LAN, and 2nd Serial RS-232
Noise level	<54 dBA (ISO7779)
Power consumption	Min 5.7 W
Voltage	220V/50HZ or 110V/60HZ
Drivers	Windows 2000, Win XP, Windows 7/8/10 (32/64), Win 2003 (32/64), Win server 2008 (32/64)
Dimensions (WxDxH)	398 x 296 x 201 mm (15.67" x 11.65" x 7.91")
Weight	9 kg

OPTIONS

MICR	Recognized fonts: CMC7, E13B Speed: >30 cps (CMC7) or >18 cps (E13B)
HMSR	DIN/ISO, ANSI and IBM3604, IBM 4746, ISO7811, HT-2751-C1Z, ISO8484
RFID	Frequency: 13.56 MHz Standards: ISO 14443 A/B, ISO15693
SCANNER	A4 single/double sided, RGB 24 bit/256 greys/16 greys/BW; 600/300/200 dpi

** Product performances are referred to an appropriate use under optimal conditions. With the right to change technical specifications. The registered trademarks are the property of their respective owners.*

